



The WXS2000 Series Wood Burning Stoves offer quality construction, solid performance, and sophisticated technology to ensure a lifetime of comfortable warmth.


FEATURES

- ♠ Large rectangular door provides an expansive view of the burning fire.
- Ceramic glass for extra strength and optimum heat transfer.
- Unique, integral air wash system keeps the glass clean and clear for a wide-open view of the fire.
- Precision-cut, heavy-gauge steel provides dependable, long-lasting operation.
- High-density firebrick retains heat longer, resulting in increased efficiency.
- One-touch control ensures easy operation and comfort.
- Standard black pedestal base included.
- Optional 150-CFM blower with Dial-A-Temp speed control.
- EPA 2020 approved.
- 30 year limited warranty

STOVE CLEARANCES







S	TOVE CLEARANCES							
	WXS2016				WXS2021			
	U.S. Single-Wall Connector	U.S. Double-Wall Connector	Canada Single-Wall Connector	Canada Double-Wall Connector	U.S. Single-Wall Connector	U.S. Double-Wall Connector	Canada Single-Wall Connector	Canada Double-Wall Connector
Α	14-1/4"	12"	14-1/4"	12"	14-1/4"	12"	14-1/4"	12"
В	11-5/8"	9-3/8"	11-5/8"	9-3/8"	11-1/2"	9-1/8"	11-1/2"	9-1/8"
С	22-1/2"	19"	22-1/2"	19"	23"	19-1/2"	23"	19-1/2"
D	13-3/16"	9-5/8"	13-3/16"	9-5/8"	13-3/8"	9-5/8"	13-3/8"	9-5/8"
E	8"	8"	8"	8"	8"	8"	8"	8"
F	9"	6"	9"	6"	9"	6"	9"	6"
G	18"	15"	18"	15"	18"	15"	18"	15"
Н	37-7/16"	37-7/16"	47-7/16"	47-7/16"	37-5/8"	37-5/8"	47-5/8"	47-5/8"
I	49"	46-3/4"	51"	48-3/4"	49"	46-3/4"	51"	48-3/4"
J	34-3/4"	34-3/4"	40-7/8"	40-7/8"	34-7/8"	34-7/8"	40-7/8"	40-7/8"
K	16"	16"	18"	18"	16"	16"	18"	18"
L	0"	0"	8"	8"	0"	0"	8"	8"
М	96"	96"	96"	96"	84"	84"	84"	84"
N	61-1/2"	57-5/16"	63-1/2"	59-5/16"	61-1/2"	57-1/2"	63-1/2"	59-1/2"

STOVE SPECIFICATIONS						
WXS2016	WXS2021					
16"	20"					
2.1 gr/hr	1.6 gr/hr					
700-1,400 sq. ft. *	Up to 2,000 sq. ft. *					
55,000 BTU/hr	76,000 BTU/hr					
7-9 hours	7-9 hours					
	WXS2016 16" 2.1 gr/hr 700-1,400 sq. ft. * 55,000 BTU/hr					

STOVE DIMENSIONS					
WXS2016	WXS2021				
24-3/8"	25-7/8"				
30-1/4"	30-3/8"				
19-3/8"	23-3/8"				
280 lbs.	316 lbs.				
	WXS2016 24-3/8" 30-1/4" 19-3/8"				

^{*}Square-feet heating capacities and burn times are approximations only. Actual performance may vary depending upon home design and insulation, ceiling heights, climate, condition and type of wood used, appliance location, burn rate, accessories chosen, chimney installation and how the appliance is operated.









