

# GAS INSERTS





MADISON PARK 34

The Madison Park gas fireplace insert brings convenience and efficient heating to an existing wood-burning fireplace. Listed to fit zero-clearance factory-built and masonry fireplaces, the Madison Park gas insert turns your standard wood burning fireplace into a cost-effective heat source that displays a realistic gas fire for brilliant warmth and ambiance.

## OVERVIEW

- ◆ Available in large, medium and small models to fit a wide range of fireplace sizes.
- ◆ Electronic ignition system with battery backup—still ignites and heats during a power outage.
- ◆ Outstanding heating efficiency for increased comfort and lower operating costs.
- ◆ Ceramic glass for optimum heat transfer and a protective screen\*.
- ◆ Beautifully crafted high-definition ceramic fiber log set.
- ◆ State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- ◆ Choose between several distinctive styles of accessory façades to match the look of your existing décor (required).
- ◆ Interior selections consist of black reflective porcelain or a variety of ceramic fiber liners (required).
- ◆ Factory installed blower with six speed settings to fine tune your heating needs.
- ◆ Full-function remote control included (IPI/CPI, thermostat, flame height, blower).
- ◆ 20 year limited warranty.

\*All applicable models comply with ANSI Z21.50/88 barrier requirements.



Madison Park 32 shown with Vista façade and Black Tie liner.

## MADISON PARK 34

**BTU INPUT NG:** 25,000 - 38,000  
**BTU INPUT LP:** 27,000 - 35,500  
**HEATING CAPACITY:** 500 – 2000 square feet  
**AFUE EFFICIENCY:** 67% (NG) 73% (LP)  
**ENERGUIDE (P4) EFFICIENCY:** 66% (NG) 68% (LP)  
**BLOWER:** 150-CFM  
**REMOTE CONTROL:** Standard

## MADISON PARK 32

**BTU INPUT NG:** 23,000 - 34,000  
**BTU INPUT LP:** 28,000 - 34,000  
**HEATING CAPACITY:** 500 – 1,750 square feet  
**AFUE EFFICIENCY:** 71% (NG) 74% (LP)  
**ENERGUIDE (P4) EFFICIENCY:** 65% (NG) 70% (LP)  
**BLOWER:** 150-CFM  
**REMOTE CONTROL:** Standard

## MADISON PARK 27

**BTU INPUT NG:** 18,000 - 25,000  
**BTU INPUT LP:** 16,000 - 22,500  
**HEATING CAPACITY:** 450 – 1,625 square feet  
**AFUE EFFICIENCY:** 78% (NG) 75% (LP)  
**ENERGUIDE (P4) EFFICIENCY:** 73% (NG) 73% (LP)  
**BLOWER:** 150-CFM  
**REMOTE CONTROL:** Standard

# OPTIONS

## FAÇADES

Choose a face style that's right for your home.



Vista Façade



Full View Façade

## DECORATIVE ACCENT TRIMS



Vista – Vista Trim



Full View – Highliner



Full View – Frontier



Full View – Iron Rail

## LINER



Black Tie



Heritage Brown



Porcelain



Flat Black

## REMOTE



The standard Total Comfort Remote uses an integrated thermostat to keep your room at just the right temperature.



**MADISON PARK CD 34**

The Madison Park CD gas fireplace insert adds the convenience of gas with contemporary styling to an existing wood burning fireplace. Listed to fit small zero-clearance factory-built and masonry fireplaces, the Madison Park CD turns your standard wood burning fireplace into a stylish and convenient heat source that you control with the press of a button.

## OVERVIEW

- ◆ Available in large, medium and small models to fit a wide range of fireplace sizes.
- ◆ Electronic ignition system with battery backup—still ignites and heats during a power outage.
- ◆ Outstanding heating efficiency for increased comfort and lower operating costs.
- ◆ Ceramic glass for optimum heat transfer and a protective screen\*.
- ◆ State-of-the-art burn technology and glass floor media provide a stunning flame presentation.
- ◆ Choose between several distinctive styles of accessory façades to match the look of your existing décor (required).
- ◆ Interior selections consist of black reflective porcelain or a variety of ceramic fiber liners (required).
- ◆ Reflective black crushed glass media included with several optional colors available to customize the look
- ◆ Factory installed blower with six speed settings to fine tune your heating needs.
- ◆ Full-function remote control included (IPI/CPI, thermostat, flame height, blower).
- ◆ 20 year limited warranty.

\*All applicable models comply with ANSI Z21.50/88 barrier requirements.



Madison Park CD shown with Vista Façade and Porcelain Liner.

## MADISON PARK CD 34

**BTU INPUT NG:** 25,000 - 38,000  
**BTU INPUT LP:** 27,000 - 35,500  
**HEATING CAPACITY:** 500 – 2000 square feet  
**AFUE EFFICIENCY:** 68% (NG) 70% (LP)  
**ENERGUIDE (P4) EFFICIENCY:** 66% (NG) 70% (LP)  
**BLOWER:** 150-CFM  
**REMOTE CONTROL:** Standard

## MADISON PARK CD 32

**BTU INPUT NG:** 23,000 - 34,000  
**BTU INPUT LP:** 28,000 - 34,000  
**HEATING CAPACITY:** 500 – 1,750 square feet  
**AFUE EFFICIENCY:** 72% (NG) 74% (LP)  
**ENERGUIDE (P4) EFFICIENCY:** 67% (NG) 72% (LP)  
**BLOWER:** 150-CFM  
**REMOTE CONTROL:** Standard

## MADISON PARK CD 27

**BTU INPUT NG:** 21,000 - 30,000  
**BTU INPUT LP:** 20,000 - 25,000  
**HEATING CAPACITY:** 500 – 1,500 square feet  
**AFUE EFFICIENCY:** 67% (NG) 69% (LP)  
**ENERGUIDE (P4) EFFICIENCY:** 66% (NG) 68% (LP)  
**BLOWER:** 150-CFM  
**REMOTE CONTROL:** Standard

# OPTIONS

## FAÇADES

Choose a face style that's right for your home.



Vista Façade



Full View Façade

## DECORATIVE ACCENT TRIMS



Vista – Vista Trim



Full View – Highliner



Full View – Frontier



Full View – Iron Rail

## LINER



Black Tie



Heritage Brown



Porcelain



Flat Black

## GLASS MEDIA



Reflective Black (Std)



Platinum



Reflective Blue

## REMOTE



The standard Total Comfort Remote uses an integrated thermostat to keep your room at just the right temperature.



**RAVENNA 40**

The Ravenna gas fireplace insert offers the convenience of gas, the look of a real wood fire and an efficient source of supplemental heat. Listed to fit most zero-clearance factory-built and masonry fireplaces, the Ravenna turns your standard fireplace into a cost-effective heat source and warm, beautiful gathering place.

## OVERVIEW

- ◆ Available in a medium size to fit most common fireplace sizes.
- ◆ Electronic ignition models include a battery backup—still ignites and heats during a power outage.
- ◆ Outstanding heating efficiency for increased comfort and lower operating costs.
- ◆ Ceramic glass for optimum heat transfer and a protective screen\*.
- ◆ Beautifully crafted high-definition ceramic fiber log set.
- ◆ State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- ◆ Interior selection consists of a natural tan brick ceramic fiber liner (required).
- ◆ Factory installed blower with six speed settings to fine tune your heating needs.
- ◆ Full-function remote control included (IPI/CPI, thermostat, flame height, blower).
- ◆ 20 year limited warranty.

\*All applicable models comply with ANSI Z21.50/88 barrier requirements.



Ravenna 40 shown with Contemporary face and Tan Brick liner.

## RAVENNA 40

- BTU INPUT NG:** 28,000 - 40,000
- BTU INPUT LP:** 26,000 - 37,500
- HEATING CAPACITY:** 500 – 2000 square feet
- ENERGUIDE (P4) EFFICIENCY:** 67% (NG) 69% (LP)
- BLOWER:** 150-CFM
- REMOTE CONTROL:** Standard

## RAVENNA 33

- BTU INPUT NG:** 24,000 - 33,000
- BTU INPUT LP:** 24,000 - 33,000
- HEATING CAPACITY:** 500 – 2000 square feet
- ENERGUIDE (P4) EFFICIENCY:** 66% (NG) 68% (LP)
- BLOWER:** 150-CFM
- REMOTE CONTROL:** Standard

# OPTIONS

## FACE STYLE & FINISH



Contemporary  Black

## LINER



Tan Brick

## SURROUND AND TRIM

Choose your surround and trim.



Standard surround



Black


Trim

## REMOTE



The standard Total Comfort Remote uses an integrated thermostat to keep your room at just the right temperature.

# SPECIFICATIONS



## DIMENSIONS

		Madison Park 27	Madison Park CD 27	Madison Park 32	Madison Park CD 32	Madison Park 34	Madison Park CD 34	Ravenna 33/40
Width	Front	26-5/8"	26-5/8"	31-5/8"	31-5/8"	33-5/8"	33-5/8"	31-1/4"
	Back/Rear	16-3/4"	16-3/4"	21"	21"	23"	23"	17-5/8"
Height	Overall	17-7/8"	17-7/8"	19-3/8"	19-3/8"	23-7/8"	23-7/8"	19-3/8"
Depth	Overall	14-7/8"	14-7/8"	15-7/8"	15-7/8"	16-1/4"	16-1/4"	15-7/8"
To Centerline (CL) of 3" Flue Collar		8-3/16"	8-3/16"	9-3/4"	9-3/4"	10"	10"	13-3/8"

## MINIMUM CLEARANCES TO COMBUSTIBLES

Hearth protection to be minimum of 3/8" thick non-combustible or equivalent, with a k factor of .84.

## CLEARANCES

		Madison Park 27 & Madison Park CD 27	Madison Park 32 & Madison Park CD 32	Madison Park 34 & Madison Park CD 34	Ravenna 33	Ravenna 40
A	1-1/2" Top facing to bottom of appliance	32"	32"	36"	31-1/2"	35-1/2"
B	Side facing or side wall to center of glass	23"	25-7/8"	26-7/8"	25-1/2"	25-1/2"
C	6" Mantel to bottom of appliance	34"	32"	36"	39"	43"
D	Vertical distance from base of appliance to hearth extension	0" 4"	0" 10"	0" 10"	0" 2" 4"	0" 2" 4"
E	Minimum horizontal distance from front of appliance	10" 0"	2" 0"	2" 0"	13" 10" 0"	14" 10" 0"

## SURROUND SIZING

	Madison Park™ 27 & Madison Park™ CD 27	Madison Park™ 32 & Madison Park™ CD 32	Madison Park™ 34 & Madison Park™ CD 34	Ravenna™ 33/40
Standard Surround 3-pc	26" H X 37" W	26" H X 41" W	31" H X 41" W	29" H X 41" W
	26" H X 41" W	26" H X 46" W	31" H X 46" W	29" H X 48" W
	30" H X 37" W	33" H X 41" W	34" H X 41" W	33" H X 41" W
	30" H X 41" W	33" H X 46" W	34" H X 46" W	33" H X 48" W
Standard Surround 1-pc	N/A	N/A	N/A	29" H X 41" W
4 Sided - Able to be Trimmed	38" H X 46" W	38" H X 46" W	42" H X 46" W	N/A
Cast Surround	N/A	N/A	N/A	30" H X 45-1/2" W

## FIREPLACE SIZING

	Madison Park™ 27 & Madison Park™ CD 27	Madison Park™ 32 & Madison Park™ CD 32	Madison Park™ 34 & Madison Park™ CD 34	Ravenna™ 33/40
Front Width	27"	32"	34"	31-1/2"
Height	18"	19-1/2"	24"	19-1/2"
Rear Width	17"	22"	24"	18"
Depth	15"	16"	16"	16"