

GAS INSERTS





MADISON PARK 34

The Madison Park gas fireplace insert brings convenience and efficient heating to an existing wood-burning fireplace. Listed to fit zero-clearance factory-built and masonry fireplaces, the Madison Park gas insert turns your standard wood burning fireplace into a cost-effective heat source that displays a realistic gas fire for brilliant warmth and ambiance.

OVERVIEW

- ♦ Available in large, medium and small models to fit a wide range of fireplace sizes.
- ♦ Electronic ignition system with battery backup—still ignites and heats during a power outage.
- ♦ Outstanding heating efficiency for increased comfort and lower operating costs.
- ♦ Ceramic glass for optimum heat transfer and a protective screen*.
- ♦ Beautifully crafted high-definition ceramic fiber log set.
- ♦ State-of-the-art burn technology provides the warm glowing appearance of an authentic fire.
- ♦ Choose between several distinctive styles of accessory façades to match the look of your existing décor (required).
- ♦ Interior selections consist of black reflective porcelain or a variety of ceramic fiber liners (required).
- ♦ Factory installed blower with six speed settings to fine tune your heating needs.
- ♦ Full-function remote control included (IPI/CPI, thermostat, flame height, blower).
- ♦ 20 year limited warranty.

*All applicable models comply with ANSI Z21.50/88 barrier requirements.



Madison Park 32 shown with Vista façade and Black Tie liner.

MADISON PARK 34

BTU INPUT NG: 25,000 - 38,000
BTU INPUT LP: 27,000 - 35,500
HEATING CAPACITY: 500 – 2000 square feet
AFUE EFFICIENCY: 67% (NG) 73% (LP)
ENERGUIDE (P4) EFFICIENCY: 66% (NG) 68% (LP)
BLOWER: 150-CFM
REMOTE CONTROL: Standard

MADISON PARK 32

BTU INPUT NG: 23,000 - 34,000
BTU INPUT LP: 28,000 - 34,000
HEATING CAPACITY: 500 – 1,750 square feet
AFUE EFFICIENCY: 71% (NG) 74% (LP)
ENERGUIDE (P4) EFFICIENCY: 65% (NG) 70% (LP)
BLOWER: 150-CFM
REMOTE CONTROL: Standard

MADISON PARK 27

BTU INPUT NG: 18,000 - 25,000
BTU INPUT LP: 16,000 - 22,500
HEATING CAPACITY: 450 – 1,625 square feet
AFUE EFFICIENCY: 78% (NG) 75% (LP)
ENERGUIDE (P4) EFFICIENCY: 73% (NG) 73% (LP)
BLOWER: 150-CFM
REMOTE CONTROL: Standard

OPTIONS

FAÇADES

Choose a face style that's right for your home.



Vista Façade



Full View Façade

DECORATIVE ACCENT TRIMS



Vista – Vista Trim



Full View – Highliner



Full View – Frontier



Full View – Iron Rail

LINER



Black Tie



Heritage Brown



Porcelain




Flat Black

REMOTE



The standard Total Comfort Remote uses an integrated thermostat to keep your room at just the right temperature.

SPECIFICATIONS



DIMENSIONS

		Madison Park 27	Madison Park 32	Madison Park 34
Width	Front	26-5/8"	31-5/8"	33-5/8"
	Back/Rear	16-3/4"	21"	23"
Height	Overall	17-7/8"	19-3/8"	23-7/8"
Depth	Overall	14-7/8"	15-7/8"	16-1/4"
To Centerline (CL) of 3" Flue Collar		8-3/16"	9-3/4"	10"

CLEARANCES

MINIMUM CLEARANCES TO COMBUSTIBLES Hearth protection to be minimum of 3/8" thick non-combustible or equivalent, with a k factor of .84.

		Madison Park 27	Madison Park 32	Madison Park 34
A	1-1/2" Top facing to bottom of appliance	32"	32"	36"
B	Side facing or side wall to center of glass	23"	25-7/8"	26-7/8"
C	6" Mantel to bottom of appliance	34"	32"	36"
D	Vertical distance from base of appliance to hearth extension	0" 4"	0" 10"	0" 10"
E	Minimum horizontal distance from front of appliance	10" 0"	2" 0"	2" 0"

SURROUND SIZING

	Madison Park™ 27	Madison Park™ 32	Madison Park™ 34
Standard Surround 3-pc	26" H X 37" W	26" H X 41" W	31" H X 41" W
	26" H X 41" W	26" H X 46" W	31" H X 46" W
	30" H X 37" W	33" H X 41" W	34" H X 41" W
	30" H X 41" W	33" H X 46" W	34" H X 46" W
Standard Surround 1-pc	N/A	N/A	N/A
4 Sided - Able to be Trimmed	38" H X 46" W	38" H X 46" W	42" H X 46" W
Cast Surround	N/A	N/A	N/A

FIREPLACE SIZING

	Madison Park™ 27	Madison Park™ 32	Madison Park™ 34
Front Width	27"	32"	34"
Height	18"	19-1/2"	24"
Rear Width	17"	22"	24"
Depth	15"	16"	16"