

ALLUME See Through

LINEAR DIRECT VENT GAS FIREPLACES

astria
FIREPLACES®



STANDARD FEATURES

- ◆ Available in 60", 72", and 84" linear configured models
- ◆ HeatFlo™ kit option allows heat to be directed above heat sensitive wall hangings
- ◆ Electronic ignition with battery backup provides continued operation in the event of a power outage
- ◆ Clean-face design with integrated tile stops for easy finishing
- ◆ Ceramic glass for optimum heat transfer and a protective screen*
- ◆ Black painted interior standard with multiple glass liner options available
- ◆ Reflective black crushed glass media included with several optional colors available to customize the look
- ◆ Wireless wall-mounted control provides variable flame settings
- ◆ Limited Lifetime Warranty

*All applicable models comply with ANSI Z21.50/88 barrier requirements.

LINERS



Black Painted (Standard)




Black Reflective



White Reflective

MEDIA




Refl. Black Crushed Glass
(Standard)



Platinum Crushed Glass



Refl. Blue Crushed Glass



Onyx Ice Rock



Diamond Ice Rock



Sapphire Blue Ice Rock



River Rock Assorted Set



High-Definition
Driftwood Log Set






- Wireless Wall-Mounted Control (Standard)
- Multi-Function Touch Remote (Optional)
- Hand-Held On/Off High/Low Remote Control (Optional)

astria.us.com

APPLIANCE SPECIFICATIONS

FLAT WALL FRAMING SPECIFICATIONS



ALLUME ST FRAMING DIMENSIONS

Models	A	B	C	E	F	G	H
60" See Through Framing	74-1/4"	18-1/2"	48-1/2"	84"	—	—	—
60" See Through Framing HeatFlo™ Kit	74-1/4"	18-1/2"	48-1/2"	84"	3"	62"	7-1/2"
72" See Through Framing	86-1/4"	18-1/2"	48-1/2"	84"	—	—	—
72" See Through Framing HeatFlo™ Kit	86-1/4"	18-1/2"	48-1/2"	84"	3"	78"	7-1/2"
84" See Through Framing	98-1/4"	18-1/2"	48-1/2"	84"	—	—	—
84" See Through Framing HeatFlo™ Kit	98-1/4"	18-1/2"	48-1/2"	84"	3"	90"	7-1/2"

E. MINIMUM HEIGHT FROM APPLIANCE BASE TO CEILING

F. MINIMUM OPENING DISTANCE FROM CEILING TO ALLOW FOR MIN DISTANCE FROM HEATFLO REGISTER TO CEILING OF 6"

Refer to Spec Sheet for complete see-through applications and instructions.

Refer to Installation Manual for all required clearances to combustibles.

FIREPLACE BTU OPERATING RANGE

MODEL	FUEL	BTU/HR	AFUE	P4
ALLUME ST 60-B	NG	40,000-28,000	52.6	55.1
ALLUME ST 60-B	LP	40,000-30,000	52.6	54.0
ALLUME ST 72	NG	45,000-31,500	55.0	57.0
ALLUME ST 72	LP	43,000-32,250	55.0	57.8
ALLUME ST 84	NG	50,000-35,000	51.1	55.4
ALLUME ST 84	LP	47,000-35,250	56.7	63.1

IMPORTANT NOTES:

As with any fireplace, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer. Local conditions, such as elevation and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, ceiling height, accessories chosen and appliance location. Diagrams, illustrations and photographs are not to scale — consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.

astria
FIREPLACES®