

# MADISON PARK CD



SHOWN: MADISON PARK CD 34

## OVERVIEW

- ◆ Available in large, medium and small models to fit a wide range of fireplace sizes.

---

- ◆ Electronic ignition system with battery backup—still ignites and heats during a power outage.

---

- ◆ Outstanding heating efficiency for increased comfort and lower operating costs.

---

- ◆ Ceramic glass for optimum heat transfer and a protective screen\*.

---

- ◆ State-of-the-art burn technology and glass floor media provide a stunning flame presentation.

---

- ◆ Choose between several distinctive styles of accessory façades to match the look of your existing décor (required).

---

- ◆ Interior selections consist of black reflective porcelain or a variety of ceramic fiber liners (required).

---

- ◆ Reflective black crushed glass media included with several optional colors available to customize the look

---

- ◆ Factory installed blower with six speed settings to fine tune your heating needs.

---

- ◆ Full-function remote control included (IPI/CPI, thermostat, flame height, blower).

---

- ◆ 20 year limited warranty.

\*All applicable models comply with ANSI Z21.50/88 barrier requirements.

## OPTIONS

### FACADES



Vista Façade



Full View Façade

### ACCENT TRIMS



Vista - Vista Trim



Full View - Highliner



Full View - Frontier




Full View - Iron Rail

### LINERS



Black Tie



Heritage Brown

### GLASS MEDIA



Reflective Black (Std)



Porcelain



Flat Black



Platinum



Refl. Blue

# SPECIFICATIONS

## PRODUCT DIMENSIONS

		Madison Park CD 27	Madison Park CD 32	Madison Park CD 34
Width	Front	26-5/8"	31-5/8"	33-5/8"
	Back/Rear	16-3/4"	21"	23"
Height	Overall	17-7/8"	19-3/8"	23-7/8"
	Depth	14-7/8"	15-7/8"	16-1/4"
To Centerline (CL) of 3" Flue Collar		8-3/16"	9-3/4"	10"

## CLEARANCES

### MINIMUM CLEARANCES TO COMBUSTIBLES

		Madison Park CD 27	Madison Park CD 32	Madison Park CD 34
A	1-1/2" Top facing to bottom of appliance	32"	32"	36"
B	Side facing or side wall to center of glass	23"	25-7/8"	26-7/8"
C	6" Mantel to bottom of appliance	34"	32"	36"
D	Vertical distance from base of appliance to hearth extension	0" 4"	0" 10"	0" 10"
E	Minimum horizontal distance from front of appliance	10" 0"	2" 0"	2" 0"

Hearth protection to be minimum of 3/8" thick non-combustible or equivalent, with a k factor of .84.


## SURROUND SIZING

	Madison Park CD 27	Madison Park CD 32	Madison Park CD 34
Standard Surround 3-pc	26" H X 37" W	26" H X 41" W	31" H X 41" W
	26" H X 41" W	26" H X 46" W	31" H X 46" W
	30" H X 37" W	33" H X 41" W	34" H X 41" W
	30" H X 41" W	33" H X 46" W	34" H X 46" W
Standard Surround 1-pc	N/A	N/A	N/A
4 Sided - Able to be Trimmed	38" H X 46" W	38" H X 46" W	42" H X 46" W
Cast Surround	N/A	N/A	N/A

## FIREPLACE SIZING

	Madison Park CD 27	Madison Park CD 32	Madison Park CD 34
Front Width	27"	32"	34"
Height	18"	19-1/2"	24"
Rear Width	17"	22"	24"
Depth	15"	16"	16"

## DIAGRAMS



## MADISON PARK CD 27

**BTU INPUT NG:** 21,000 - 30,000

**BTU INPUT LP:** 20,000 - 25,000

**HEATING CAPACITY:** 500 – 1,500 square feet

**AFUE EFFICIENCY:** 67% (NG) 69% (LP)

**ENERGUIDE (P4) EFFICIENCY:** 66% (NG) 68% (LP)

**BLOWER:** 150-CFM

**REMOTE CONTROL:** Standard

## MADISON PARK CD 32

**BTU INPUT NG:** 23,000 - 34,000

**BTU INPUT LP:** 28,000 - 34,000

**HEATING CAPACITY:** 500 – 1,750 square feet

**AFUE EFFICIENCY:** 72% (NG) 74% (LP)

**ENERGUIDE (P4) EFFICIENCY:** 67% (NG) 72% (LP)

**BLOWER:** 150-CFM

**REMOTE CONTROL:** Standard

## MADISON PARK CD 34

**BTU INPUT NG:** 25,000 - 38,000

**BTU INPUT LP:** 27,000 - 35,500

**HEATING CAPACITY:** 500 – 2000 square feet

**AFUE EFFICIENCY:** 68% (NG) 70% (LP)

**ENERGUIDE (P4) EFFICIENCY:** 66% (NG) 70% (LP)

**BLOWER:** 150-CFM

**REMOTE CONTROL:** Standard

