MONTECITO

HIGH EFFICIENCY WOOD BURNING FIREPLACES





STANDARD FEATURES

- Circulating design features facade, arch doors and ceramic glass for optimum heat transfer
- EPA variable-rate certified high-efficiency wood heater
- lacktriangle 2.0 cubic foot insulated firebox that accepts up to 19" log size for increased performance
- lacktriangle Stacked textured refractory panels with integrated ash lip and decorative cast iron log retainer
- 💠 Air combustion control for variable heat output with air boost for faster wood ignition during startup
- Includes insulated outside air kit (required for use)
- 55,000 BTUs and heats up to 1,500 square feet*
- * Efficient air wash system that keeps glass clean
- lacktriangle Cast or steel door available with heat resistant door handle that stays cool to the touch
- ♦ Includes heat activated 200 CFM variable-speed blower for time-delayed heat distribution
- ♣ HeatFlo™ air kit and/or thermostatically controlled forced air kit available (three maximum outlets)
- Durable high temperature paint finish
- Limited Lifetime Warranty

DOORS (One Required)



Cast-Iron



Smooth

FACADE (Required)




Smooth


BRICK




Textured Stacked Panels

APPLIANCE SPECIFICATIONS












As with any fireplace, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer.

Local conditions, such as elevation, wind, vent configuration and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, climate, condition and type of fuel used, appliance location, burn rate, accessories chosen, chimney installation and how the appliance is operated.

Diagrams, illustrations and photographs are not to scale—consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.







PRODUCT SPECIFICATIONS

Glass Viewing Area (W x H)	22-1/2" x 12-1/4"
Firebox Interior (W x H x D)	22" x 11-3/4" x 12"
Interior Cubic Feet	2.0
Maximum Log Size	19"
EPA Rating	1.9 grams/hr
Max BTU's	55,000
Heating Capacity (up to)	1,500 sq. ft.
Thermal Efficiency	72%
Blower	200 CFM





