

The DRL4000 Series linear direct vent gas fireplace offers a sleek modern appearance that is right at home in contemporary and transitional spaces. An expansive ceramic glass opening provides an exceptional view of the gently dancing flames rising through the beautiful reflective black glass floor media. Add the optional heat circulating blower and multi-function remote for the ultimate in comfort and control.



FEATURED DRL4060 shown with black painted interior and black reflective crushed glass

STANDARD FEATURES

- Available in 48", 60", 72", and 84" linear configured models
- See through conversion kit available to allow viewing from two living spaces
- HeatFlo kit option allows heat to be directed above heat sensitive wall hangings
- Electronic ignition with battery backup provides continued operation in the event of a power outage
- Clean-face design with integrated tile stops for easy finishing
- Ceramic glass for optimum heat transfer and a protective screen*
- Black painted interior standard with a reflective glass liner option available
- Reflective black crushed glass media included with several optional colors available to customize the look
- Optional blower and hand held multi-function remote control available
- 20-year limited warranty



^{*}All applicable models comply with ANSI Z21.88 barrier requirements.

^{**}Blower use is not compatible with a see-through application.

INTERIOR

Liner



Black Painted Interior (Standard)



Reflective Black Glass Liner

Media



Reflective Black **Crushed Glass** (Standard)



Platinum Crushed Glass



High-Definition Driftwood Log Set



Reflective Blue Crushed Glass



River Rock Assorted Set


SEE-THROUGH KIT

TRIM

REMOTE



See-Through Kit



Black Perimeter Trim Kit



On/Off Thermostat Remote


HEATFLO KIT


Protect heat sensitive televisions, artwork and other decorative wall materials. No blower required, the HeatFlo kit works through natural convection to redirect heat from the fireplace upward through hidden ductwork and out through a sleek horizontal vent. Walls stay cooler and heat flows more evenly through the room for a comfortable fireplace experience.


- TV & Artwork can be placed above the fireplace
- Helps protect heat sensitive wall facing materials
- Improves convective heat circulation in the room
- No electricity or blower required for operation




48" MODEL








60", 72", & 84" MODELS








RIGHT SIDE VIEW

DRL 4000 SERIES DIMENSIONS

Models	А	В	С	D	E
48"	54-1/4"	27-1/8"	46"	50-3/8"	57-7/16"
60"	74"	37"	56-5/8"	61-1/2"	76-5/8"
72"	86"	43"	68-5/8"	73-1/2"	88-5/8"
84"	98"	49"	80-5/8"	85-1/2"	100-5/8"

REFER TO INSTALLATION MANUAL FOR ALL REQUIRED CLEARANCES TO COMBUSTIBLES.

On the Cover: DRL4072 fireplace with black painted interior, driftwood log set, and black crushed glass media



DRL 4000 SERIES FRAMING DIMENSIONS

Models	Α	В	С	E	F	G	н	
48" One Sided Framing HeatFlo Kit	55-5/8"	19-1/2"	39-1/8"	84"	1-1/2"	53-1/2"	5-1/8"	
60" One Sided Framing HeatFlo Kit	74-1/4"	19-1/2"	48-1/2"	84"	3"	62"	7-1/2"	
72" One Sided Framing HeatFlo Kit	86-1/4"	19-1/2"	48-1/2"	84"	3"	78"	7-1/2"	
84" One Sided Framing HeatFlo Kit	98-1/4"	19-1/2"	48-1/2"	84"	3"	90"	7-1/2"	

- E. Minimum height from appliance base to ceiling
- F. Minimum Opening Distance from Ceiling to Allow for Min Distance from HeatFlo Register to Ceiling of 6"
- REFER TO MANUAL FOR COMPLETE SEE-THROUGH APPLICATION FRAMING DIMENSIONS AND MORE.

FIREPLACE BTU OPERATING RANGE							
MODEL	FUEL	BTU/HR	AFUE	P4			
DRL 4048	NG	35,000-23,500	63.0	62.5			
DRL 4048	LP	31,000-25,500	63.0	62.4			
DRL 4060-B	NG	40,000-28,000	52.6	55.1			
DRL 4060-B	LP	40,000-30,000	52.6	54.0			
DRL 4072	NG	45,000-31,500	55.0	57.0			
DRL 4072	LP	43,000-32,250	55.0	57.8			
DRL 4084	NG	50,000-35,000	51.1	55.4			
DRL 4084	LP	47,000-35,250	56.7	63.1			

IMPORTANT NOTES:

As with any fireplace, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer.

Local conditions, such as elevation and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, ceiling height, accessories chosen and appliance location.

Diagrams, illustrations and photographs are not to scale — consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.





