

INSTALLATION INSTRUCTIONS FOR UNIVERSAL REPLACEMENT CONVECTION BLOWER KIT

KIT CONTENTS

- 1 ea. Convection Blower Assembly
- 3 ea. Nut, 10/24 K-Lock, Plated
- 2 ea. Butt Connector (4X312)
- 3 ea. Screws, 10-24 x 3/4 Socket Head Cap
- 3 ea. Washers, #10 SAE
- 1 ea. Gasket, Convection Blower
- 1 ea. Instruction Sheet

TOOLS NEEDED (NOT SUPPLIED)

- Crimping tool
- Wire cutters
- 5/32" Allen key
- 5/16 Nut Driver

CONVECTION BLOWER KIT *	
Cat. No.	Kit Name
H7619	Convection Blower Kit

Table 1

GENERAL INFORMATION

This kit replaces the following kits (cat. no's): 12146109, H5884, 52L02, H5888, and H7309

If you encounter any problems, need clarification of these instructions or are not qualified to properly install this kit, contact your local distributor or dealer.

Read this instruction sheet in its entirety before beginning the installation.

ALL WARNINGS, PRECAUTIONS AND INSTRUCTIONS IN THE INSTALLATION AND OPERATION MANUAL PROVIDED WITH THE APPLIANCE APPLY TO THESE INSTRUCTIONS.

Check the contents of the kits upon receipt and check for any damaged or missing parts. If there is hidden damage, notify your freight company or Innovative Hearth Products (IHP) dealer immediately.

CAUTION: Wear gloves during installation in case of sharp edges on the stove.

INSTALLER: Leave this manual with the appliance
CONSUMER: Retain this manual for future reference

WARNING

ELECTRICAL GROUNDING INSTRUCTIONS This appliance is equipped with a three-prong (grounding) plug for your protection against shock hazard and should be plugged directly into a properly grounded three-prong receptacle. The appliance must be electrically grounded in accordance with local codes or, in the absence of local codes, the National Electrical Code, ANSI/NFPA 70-(latest edition). (In Canada, the current CSA C22-1 Canadian Electrical Code.)

WARNING

This kit must be installed by a qualified installer, service agency, or gas supplier. These instructions must be used in conjunction with the installation and operation manual provided with the fireplace.

INSTALLATION INSTRUCTIONS

1. To use this replacement blower kit first turn off all power to your appliance.
2. Cut the wires to the blower being replaced.
3. Note the location of the mounting screws, and remove the old blower and gasket. Discard in a manner suitable to your locality.
4. Strip the leads of the wires to the unit, removing approximately 3/8" of insulation per wire.
5. Using the previous locations, attach the replacement blower and gasket using the screws, washers, and nuts provided.
6. Connect each wire from the new blower to the wires from appliance, using the butt connectors provided. The wires to the blower are not polarity sensitive.
7. Turn the power to the appliance back on.
8. Confirm that the blower operates.

Innovative Hearth Products (IHP) reserves the right to make changes at any time, without notice, in design, materials, specifications, prices and also to discontinue colors, styles and products. Consult your local distributor for fireplace code information.