

# GEORGETOWN 300

## WOOD STOVES

**COUNTRY STOVES**  
A LIFETIME OF WARMTH



**GEORGETOWN 300 (Legs Style)**

**LOG LENGTH:** 21" max.

**HEATING CAPACITY:** 2,000-3,000 square feet

**MAXIMUM OUTPUT:** 100,000 BTU/hour

**EFFICIENCY:** 80%



**GEORGETOWN 300 (Pedestal Style)**

### STANDARD FEATURES

- Thermal Fin heat exchanger creates 32% more surface area than a standard stove design resulting in more heat entering the room.
- Air-boost timer automatically adjusts the air intake control making startup and reloading easier.
- Tall opening provides an expansive view of the burning fire.
- Ceramic glass for extra strength and optimum heat transfer.
- Unique, integral air wash system keeps the glass clean and clear for a wide-open view of the fire.
- Precision-cut, heavy-gauge steel provides dependable, long-lasting operation.
- High-density firebrick retains heat longer, resulting in increased efficiency.
- One-touch control ensures easy operation and comfort.
- EPA-certified for clean and efficient operation.
- Limited lifetime warranty.

### OPTIONS

#### LEG/PEDESTAL STYLE



Brushed Nickel  
Nickel  
Standard Black

Cast Olympic Leg



Brushed Nickel  
Standard Black

Cast Coastal Leg



Standard Black

Lakeview Steel Leg



Cast Coastal Leg with Ash drawer



Pedestal with Ash drawer



Pedestal

#### LOUVER FINISH



Brushed Nickel



Standard Black


#### DOOR TRIM



Brushed Nickel  
Nickel  
Standard Black

SPECIFICATIONS

SIDE WALL/BACK WALL Fig. 1




F†= Measured from corner of stove heat shield.


\*Measured from door opening.

\*\*Clearances to flue are from the stove flue collar to combustibles.

CORNER Fig. 2



ALCOVE Fig. 3



PRODUCT DIMENSIONS

|                    |               | GEORGETOWN 300 |
|--------------------|---------------|----------------|
| Width              |               | 26-1/2"        |
|                    | Lakeview Legs | 33-15/16"      |
|                    | Coastal Legs  | 33-5/8"        |
|                    | Olympic Legs  | 34-5/8"        |
|                    | Pedestal      | 36-1/8"        |
| Depth              |               | 29-5/16"       |
| Stovepipe Diameter |               | 6"             |

CLEARANCES

|                               | GEORGETOWN 300           |                          |                              |                              |
|-------------------------------|--------------------------|--------------------------|------------------------------|------------------------------|
|                               | US Single-Wall Connector | US Double-Wall Connector | Canada Single-Wall Connector | Canada Double-Wall Connector |
| D**= Flue Collar to Back Wall | 16"                      | 11-5/8"                  | 16"                          | 11-5/8"                      |
| N**= Flue Collar to Side Wall | 25-1/8"                  | 23-1/8"                  | 25-1/8"                      | 23-1/8"                      |
| G**= Flue Collar to Wall      | 17"                      | 16"                      | 17"                          | 16"                          |

HEARTH PROTECTION

|                                |         |          |         |          |
|--------------------------------|---------|----------|---------|----------|
| E = Back of Stove              | 0"      | 0"       | 8"      | 8"       |
| F† = Stove Corner to Wall      | 6"      | 5"       | 6"      | 5"       |
| H = Pad Depth Minimum          | 41-1/8" | 41-1/8"  | 51-1/8" | 51-1/8"  |
| I = Pad Depth to Back Wall     | 53-1/2" | 49-1/8"  | 55-1/2" | 51-1/8"  |
| J = Pad Width Minimum          | 33"     | 33"      | 42-1/2" | 42-1/2"  |
| K = Front of Stove             | 16"     | 16"      | 18"     | 18"      |
| L = Measured from Door Opening | 8"      | 8"       | 12-3/8" | 12-3/8"  |
| M = Measured to Sides of Unit  | 3-5/8"  | 3-5/8"   | 8"      | 8"       |
| T = Pad Depth to Corner        | 62-7/8" | 61-7/16" | 64-7/8" | 63-7/16" |

ALCOVES

|     |                | GEORGETOWN 300 |
|-----|----------------|----------------|
| X = | Minimum Width  | 54"            |
| Y = | Maximum Depth  | 48"            |
| Z = | Minimum Height | 90"            |

F†= Measured from corner of stove heat shield.

\*Square-foot heating capacities and burn times are approximations only. Actual performance may vary depending upon home design and insulation, ceiling heights, climate, condition and type of wood used, appliance location, burn rate, accessories chosen, chimney installation and how the appliance is operated.

\*\*Clearances to flue are from the stove flue collar to combustibles. \*\*\*Depending on the type of wood being burned and the amount of heat required.

IMPORTANT NOTES:

As with any heating appliance, fireplace or stove, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer. Actual performance may vary depending upon home design and insulation, ceiling heights, climate, condition and type of wood used, appliance location, burn rate, accessories chosen, chimney installation and how the appliance is operated. Grandview Z30 approved for mobile home use. Diagrams, illustrations and photographs are not to scale-consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.