

VENT-FREE GAS LOGS

COMPLETE COLLECTION

Superior
FIREPLACES®



99% HEATING EFFICIENCY

Maximum warmth, minimal waste.



NO VENTING REQUIRED

Keep the heat in where it belongs.



NO CHIMNEY HEAT LOSS

More heat for your home, not the outdoors.



POWER OUTAGE RELIABILITY

Enjoy warmth and comfort even when the power is out.



CLEAN-BURNING DESIGN

Better for your home and the environment.

NATURE-FLAME SERIES



GRANITE RIDGE



EMBERWOOD SPLIT



HIGHRIDGE BIRCH



SILVERSTONE TIMBER

MEGA-FLAME SERIES



MOSSY OAK



GIANT TIMBERS

TRIPLE-FLAME SERIES



WILD TIMBER



RUGGED STACK

DOUBLE-FLAME SERIES



CRESCENT HILL HD



CRESCENT HILL

MEGA-FLAME OUTDOOR SERIES



GIANT TIMBERS



MOSSY OAK



GOLDEN OAK



INDOOR & OUTDOOR MODELS

Options to fit your indoor or outdoor space.



NATURAL GAS & LP OPTIONS

Compatible with Natural Gas (NG) and Liquid Propane (LP).



MULTIPLE CONTROL OPTIONS

Millivolt, Variable, or Electronic ignition models

SPECIFICATIONS

SERIES	LOG SIZE	BURNER SIZE	MINIMUM FIREBOX DIMENSIONS				CONTROLS & BTUs					
			FRONT WIDTH	REAR WIDTH	HEIGHT	DEPTH	MILLIVOLT		VARIABLE		ELECTRONIC	
							NG	LP	NG	LP	NG	LP
MEGA-FLAME	24"	24"	32-1/4"	22-3/4"	28"	15-1/2"	40K-29K	40K-29K	38K-28K	39K-31K	38K-28K	39K-31K
	30"	24"	39"	26-3/4"	28"	15-1/2"	40K-29K	40K-29K	38K-28K	39K-31K	38K-28K	39K-31K
	36"	30"	47"	33"	28"	15-1/2"	40K-29K	40K-29K	38K-28K	39K-31K	38K-28K	39K-31K
NATURE-FLAME	18"	18"	26"	17"	17"	15"	30K-21K	29K-21K	—	—	30K-22K	30K-22K
	24"	24"	29"	22"	19"	15"	39K-28K	36K-25K	—	—	39K-28K	36K-25K
	30"	24"	33"	25"	19"	15"	39K-28K	36K-25K	—	—	39K-28K	36K-25K
TRIPLE-FLAME	18"	18"	28"	20"	19"	14"	30K-21K	30K-24K	30K-21K	30K-24K	28K-24K	28K-24K
	24"	24"	30"	22"	19"	14"	39K-28K	39K-28K	39K-28K	39K-28K	39K-28K	39K-28K
	30"	24"	40"	30"	19"	14"	39K-28K	39K-28K	39K-28K	39K-28K	39K-28K	39K-28K
DOUBLE-FLAME*	18"	18"	24"	20-1/2"	17"	13-1/2"	36K-25K	36K-25K	—	—	—	—
	24"	18"	28"	20-1/2"	17"	13-1/2"	36K-25K	36K-25K	—	—	—	—
MEGA-FLAME OUTDOOR	24"	24"	32-1/4"	22-3/4"	28"	15-1/2"	40K-29K	40K-29K	—	—	40K-29K	40K-29K
	30"	24"	39"	26-3/4"	28"	15-1/2"	40K-29K	40K-29K	—	—	40K-29K	40K-29K
	36"	30"	47"	33"	28"	15-1/2"	40K-29K	40K-29K	—	—	40K-29K	40K-29K

* Manual Control Model available; NG 36K-19K, LP 36K-19K

REMOTE CONTROL OPTIONS



ProFlame T'Stat
On/Off Remote²



EcoFlow Touch Screen
Multi-Function Remote^{1,3}



TRC T'stat
On/Off Remote¹



RCKIT 4001
On/Off Remote¹



RCAF3 On/Off
Hi/Low Remote⁴

Remote Control Compatibility: 1 - Optional for Millivolt Control Models, 2 - Included with Variable Control Models, 3 - Included with Indoor Electronic Control Models, 4 - Included with Outdoor Electronic Control Models

IMPORTANT NOTES:

As with any fireplace, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer.

Local conditions, such as elevation and choice of fuel will affect overall appearance of the fire and heating performance. Performance can also vary with home design and insulation, ceiling height, accessories chosen and appliance location.

Diagrams, illustrations and photographs are not to scale — consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.

